



Pneumatic accessories


Version: 2011-01

Ball valves

Standard model with a full flow.


Material:	Brass nickel-plated
Ball:	Brass chrome-plated
Ball sealing:	Teflon (PTFE)
Spindle sealing:	NBR
Lever:	Alu, black coated
Operating temperature:	-15° C to +120° C
Range of use:	Compressed air, Water, nontoxic and unaggressive gases, heating systems, agriculture
Thread:	G-thread with ISO 228/1

Ball valve, light model, female / female thread



Thread G	DN	PN	A	B	L	Article	Order-number
1/4	8	40	85	45	37	33002	XA3.150.020
3/8	10	40	85	37	42	33003	XA3.150.021
1/2	15	32	85	40	50	33004	XA3.150.022
3/4	20	32	105	48	58	33005	XA3.150.023
1	25	25	105	52	68	33006	XA3.150.024
1 1/4	32	20	130	63	80	33007	XA3.150.025
1 1/2	40	20	130	69	93	33008	XA3.150.026
2	50	16	165	83	110	33009	XA3.150.027

Ball valve, light model, female / male thread



Thread G	DN	PN	A	B	L	Article	Order-number
1/4	8	40	85	45	44	33102	XA3.150.028
3/8	10	40	85	37	51	33103	XA3.150.029
1/2	15	32	85	40	59	33104	XA3.150.030
3/4	20	32	105	48	69	33105	XA3.150.031
1	25	25	105	52	78	33106	XA3.150.032
1 1/4	32	20	130	63	91	33107	XA3.150.033
1 1/2	40	20	130	69	103	33108	XA3.150.034
2	50	16	165	83	121	33109	XA3.150.035

We reserve the right to make changes which are in the interest of technical progress.

© by WMA Schmidt & Bittner GmbH, Baumwaide 23, D-74360 Illfeld-Auenstein, Tel. +49 7062 9066-0, Fax +49 7062 9066-20
 info@wma-sb.de or wma-sb@t-online.de, <http://www.wma-sb.de>



Pneumatic accessories


Version: 2011-01

Mini ball valves

sand blasted model.


Housing and ball:	Brass nickel-plated
Lever, turning handle:	Plastic
Ball sealing:	Teflon (PTFE)
Spindle sealing:	Viton
Lever:	Alu, black coated
Operating temperature:	-10° C to +90° C
Operating pressure:	max. 10 bar
Range of use:	Compressed air, Water, Oils, nontoxic gases

Mini ball valve with turning handle



Thread G	SW	DN	L	T	T1	Article	Order-number
1/4 internal	21	8	41.5	9.0	10.5	37301	XA3.150.014
3/8 internal	21	8	41.5	12.0	10.0	37302	XA3.150.015
1/2 internal	25	10	47.0	12.5	10.5	37303	XA3.150.016
1/4 internal/external	21	8	41.5	9.0	10.5	37311	XA3.150.017
3/8 internal/external	21	8	41.5	10.0	10.0	37322	XA3.150.018
1/2 internal/external	25	10	46.0	12.0	12.0	37333	XA3.150.019

Mini ball valve with lever



Thread G	SW	DN	A	L	T	T1	Article	Order-number
1/4 internal	21	8	68.5	41.5	9.0	10.5	37401	XA3.150.001
3/8 internal	21	8	68.5	41.5	12.0	10.0	37402	XA3.150.002
1/2 internal	25	10	68.5	47.0	12.5	10.5	37403	XA3.150.010
1/4 internal/external	21	8	68.5	41.5	9.0	10.5	37411	XA3.150.011
3/8 internal/external	21	8	68.5	41.5	10.0	10.0	37422	XA3.150.012
1/2 internal/external	25	10	68.5	47.0	12.0	12.0	37433	XA3.150.013

We reserve the right to make changes which are in the interest of technical progress.

© by WMA Schmidt & Bittner GmbH, Baumwaide 23, D-74360 Ilsfeld-Auenstein, Tel. +49 7062 9066-0, Fax +49 7062 9066-20
 info@wma-sb.de or wma-sb@t-online.de, <http://www.wma-sb.de>